DRILLING AUGERS: MACHINES 750KG-5T SUITS DRIVES: PDD-PD5



ROCK/COMBO TAPER TEETH FOR ALL GROUND CONDITIONS

THE ULTIMATE ALL PERFORMANCE AUGER No need to have two augers for different conditions. Ideal in all drilling conditions. Cut a clean clear hole in soft earth and clay and have the ultimate ripping ability in fracturable rock.





DEDICATED ROCK ROTATING ROCK PICKS FOR SHALE AND FRACTURABLE ROCK

HEAVY DUTY & EFFICIENT CUTTING HEAD FOR THE ULTIMATE ROCK DRILLING AUGER Heavy duty engineered design with high efficiency cutting heads to maximise your drilling performance. Fitted with a range of quality wear parts providing superior wear and performance.



- TRUE CUT DESIGN ENSURES A 300MM AUGER DRILLS A 300MM HOLE
- DRIVE ADAPTORS & EXTENSIONS TO MAXIMISE DRILLING DEPTH
- SHALLOW PITCH FLIGHTS FOR OPTIMUM REMOVAL OF SPOIL
- ROBUST AUGER BODY CONSTRUCTION FOR LONG LIFE
- HEAVY DUTY TUBE WITH HIGHEST GRADE STEEL
- VARIETY OF HUB OPTIONS

WEB: www.digga.com



Contact your local professional dealer or contact Digga direct



6 6 QLD. NT 4 Octal Street Yatala QLD 4207

NSW. ACT Unit 2, 36 Bluett Drive

PHONE: 1300 2 DIGGA EMAIL: info@digga.com

VIC, SA, TAS 27 Metcalf Street Smeaton Grange NSW 2567 Dandenong VIC 3175

6/15 Yampi Way Willeton WA 6155



EARTH BLADED TEETH FOR EARTH / CLAY / SHALE ALL PURPOSE FOR GENERAL DRILLING The angle and geometry of the teeth to the pilot is the key to the efficiency in which these augers perform. Available in earth or multi-facet tungsten (MFT) braised onto the face of the teeth, providing longer wear life and greater cutting performance.

Need a CUSTOM SOLUTION? Give us a CALL!

Not suited to harder fracturable rock.

	MACHINES 750KG-4.51		
MODEL	A4	RC4	DR4
DRILLING CONDITIONS	GENERAL	COMBO ROCK / EARTH	DEDICATED ROCK
HUB	65mm Round	65mm Round	65mm Round
OPTIONAL HUB	50.8mm Round 57mm Square 75mm Square	50.8mm Round 57mm Square 75mm Square	75mm Square
OVERALL LENGTH	1,200mm	1,200mm	1,200mm
FLIGHTS (LEAD)	8mm	8mm	12mm
FLIGHTS (CARRY)	8mm	8mm	10mm
TEETH	TS	TTS/TTD	19mm Rotating Rock Pick
PILOT	PM-SQ	PM-HX-3	DP-UAP-API-SA
IDEAL DRIVES	PDD-PD4	PDD-PD4	PD3-PD5
OPTIMUM DRILLING SPEEDS (RPM)			
EARTH	55-65	55-65	-
CLAY	45-55	45-55	-
SHALE (FRACTURABLE ROCK)	25-45	25-45	25-45
HEAVY ROCK	-	-	10-25
AUGER FEATURES	Double flight configuration. Heavy duty body for greater strength with larger machines provide for optimum drilling on mid sized machines.		Short flighting encourages regular removal of spoil, allowing cool air to enter the hole & regular inspection of teeth.