

Hole Digging Equipment Hand Held



FEATURES

- Power-FLEX® operator handles
- Auger-LOK® system for stuck auger removal
- Honda® GXV160 engine
- All metal centrifugal clutch
- Precision, spur gear transmission
- 1.375 inch hexagon auger drive connection
- Magura® twist grip throttle control

332H EPIC® SERIES TWO MAN HOLE DIGGER

The 332H EPIC Series hand-held Hole Digger is designed to tackle a wide range of construction related hole digging projects from simple backyard fencing to complex landscaping and soil sampling. Each is built with a time-proven transmission that includes oversized bearings, heat treated shafts and precision, machine-cut gears that has created an industry wide reputation for delivering long service life and exceptional ROI. All with the power and performance to dig up to 18 inch (457 mm) diameter holes in a wide variety of soil classifications. When an auger becomes stuck use the convenient Auger-LOK system to aid in to removing it. The exclusive Power-FLEX ergonomically-engineered, composite operator handles maximize control, strength and balance while helping to dampen vibrations. The effects of kickback and fatigue are reduced while increasing overall digging comfort, productivity and jobsite safety. For use in non-hazardous environments with the 4400 Series earth auger and extension plus the 5500 Series flighted auger extensions.

SPECIFICATIONS

Power Source	5.5 HP (4.1 Kw) Honda GXV160, 4-stroke, gas engine
Starter	Hand rewind
Fuel	Gasoline, unleaded, automotive grade
Transmission	Totally enclosed, spur gear, oil lubricated
Maximum Digging Torque	190.0 ft lbs (257.6 N.m)
Nominal Auger Rotation Speed	144.0 RPM, no load
Auger Drive Connection	1.375 inch (34.9 mm) hexagon
Available Auger Diameter Range	2.25 to 18.0 inches (57.2 to 457.2 mm)
Standard Auger Digging Length	36.0 inches (914.4 mm)
Available Auger Extensions	15.0 inch (381.0 mm), plain, tube-type 36.0 inch (914.4 mm), continuous flighted
Agency Certifications	CE
Product Dimensions (L x W x H)	58.5 x 27.0 x 22.3 inches (1485.9 x 685.8 x 566.4 mm)
Product Weight	77.0 lbs (34.9 kg), less auger

All specifications are general in nature and are not intended for specific application purposes. General Equipment Company reserves the right to make changes in design, engineering, or specifications and to add improvements or discontinue manufacture at any time without notice or obligation. Consult applicable Operator Manual before utilizing. Refer to OSHA 2207 and/or current revisions for specific safety information. Names depicted are the registered trademarks of their respective owners.

Form: GEF10121903_v1.2